

PART 2 – PRODUCTS

2.01 GENERAL

- A. All equipment and materials used shall be standard components that are regularly manufactured and utilized in the manufacturer's system.
- B. All systems and components shall have been thoroughly tested and proven in actual use.
- C. All systems and components shall be provided with the availability of a toll-free (U.S. and Canada) technical support number from the manufacturer. The number shall provide technical assistance for either the dealer/installer or the end user at no charge for as long as the product is installed.

2.02 UNSHIELDED TWISTED-PAIR POWER-VIDEO TRANSCEIVER, PASSIVE

- A. The power-video (PV) transceiver device shall be capable of transmitting and receiving baseband monochrome or color video signals over unshielded twisted-pair (UTP) telephone wire to a passive transceiver up to a distance of 750 feet (225 m).
- B. Distances up to 3,000 feet (1,000 m) shall be supported when used in conjunction with an amplified (active) receiver.
- C. The transmitting device shall accept a baseband video signal from a 75-ohm source.
- D. The receiving device shall deliver a baseband video signal capable of driving a 75-ohm load.
- E. "Up the Coax" Pan/Tilt/Zoom controls shall be supported up to 750 feet (225 m) when using this transceiver to transmit the signal to a passive receiver.
- F. The transceiver shall have built-in video transient protection without the need for a ground connection.
- G. The transceiver shall be equipped with an inline male BNC for 75-ohm camera connection.
- H. The transceiver shall be equipped with a standard 8-pin RJ45 modular jack (female).
- I. The transceiver shall be capable of utilizing 24-16 AWG (solid or stranded) UTP wire with the following EIA/TIA 568B compliant pinouts:
  - Pin 1: Video +
  - Pin 2: Video –
  - Pin 3:
  - Pin 4: Power –
  - Pin 5: Power +
  - Pin 6:
  - Pin 7: Power +
  - Pin 8: Power –

- J. The transceiver shall have a pair of 16AWG solid power leads to connect camera power.
- K. The transceiver shall route power, and video signals via UTP RJ45 for organized pass-through of power.
- L. The transceiver is to be used with Power-Video-Data Cable Integrator for organized cable management between control equipment and the wiring closet or IDF or with another power-video-data transceiver device.
- M. The transceiver shall meet or exceed the following design and performance specifications:
  - a. Have typical common-mode rejection of 60 dB between the frequencies of 15 KHz to 5 MHz.
  - b. The transceiver shall have a frequency response from DC to 5 MHz.
  - c. The transceiver shall have a typical attenuation of 0.5 dB or better.
  - d. The transceiver shall provide transient immunity per ANSI/IEEE 587C62.41.
  - e. The transceiver shall be for indoor use or for use in an environmental enclosure and allow a maximum operating temperature range of -20 to 75 degrees Celsius.
- N. The transceiver shall be capable of utilizing Category 2 or better UTP without compromising interference immunity or transmission distances.
- O. The transceiver shall have a weight of 1.0oz (30g).
- P. The transceiver shall have a body width of 0.89in (22.7mm), body length of 1.61in (41mm) and a body depth of 0.81in (20.6mm).
- Q. The transceiver shall be UL and cUL listed.
- R. The transceiver shall be CE compliant.
- S. The transceiver shall be RoHs compliant
- T. The transceiver shall be WEEE compliant
- U. The transceiver shall be provided with a limited lifetime warranty.
- V. The Unshielded Twisted-Pair Power-Video Transceiver, Passive, shall be the NVT:
  - a. NV-216A-PV or
  - b. Approved equal